

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A47L 11/283, 11/03, 11/16	A1	(11) International Publication Number: WO 99/05955 (43) International Publication Date: 11 February 1999 (11.02.99)
---	-----------	--

(21) International Application Number: **PCT/SE98/01420**(22) International Filing Date: **28 July 1998 (28.07.98)**(30) Priority Data:
9702815-3 **29 July 1997 (29.07.97)** **SE**(71)(72) Applicant and Inventor: **OLSSON, Stig [SE/SE];**
Bågskytteatan 2H, S-431 43 Mölndal (SE).(74) Agent: **CEGUMARK AB; P.O. Box 53047, S-400 14 Göteborg**
(SE).(81) Designated States: **AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DE (Utility model), DK, DK (Utility model), EE, ES, FI, GB, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).****Published***With international search report.**In English translation (filed in Swedish).*(54) Title: **DEVICE AT A CLEANING MACHINE**

(57) Abstract

The invention relates to an arrangement (1) for a cleaning machine (2) comprising a number of electrically powered rotating disks (3, 4), which carry a brush (5) and a hand-held shaft (6) with a fluid supply line (7) for the supply of cleaning fluid (43) to the aforementioned discs (3, 4). In accordance with the invention, at least two disks (3, 4) mounted in mutually opposing directions of rotation and at a relative distance from one another are so arranged as to carry a brush, etc., (5) on their respective outer free end for pressing into contact with the intended surface (8) to be cleaned. The discs (3, 4) are supported by a machine head (12) supported in such a way as to be capable of pivoting about articulations extending in pairs at an angle to one another. A fluid reservoir with a pump is capable of attachment to the shaft (6), and the fluid supply line (7) is connected to the aforementioned machine head (12).



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

Device at a cleaning machine

5 The present invention relates to an
arrangement for a cleaning machine comprising at least two
disks, mounted in mutually opposing directions of rotation
and at a relative distance from one another and so arranged
as to carry a brush or other surface treatment device on
10 their respective free end for pressing into contact with the
intended surface to be cleaned, and a hand-held shaft with a
fluid supply line for the supply of cleaning fluid to the
aforementioned discs.

When cleaning and polishing floors and other
15 surfaces inside buildings, such as stairs and corners,
problems are encountered in effectively gaining access and
handling existing heavy and cumbersome cleaning machines of
the indicated kind. Even in the case of hand-held scrubbing
brushes, problems can be encountered in effectively getting
20 into every corner and being able to handle the cleaning fluid
effectively.

Previously disclosed is the use of hand-held
cleaning machines that exhibit a disc, in conjunction with
which it is possible for wandering of the machine to occur in
25 certain positions, sometimes in the wrong direction, which
means that an effort must be made to hold the machine in
position where cleaning is to be performed. Where more than
one disc is used, wandering can also take place if the discs
are so arranged as to rotate in the same direction of
30 rotation. Also previously disclosed is the use of hand-held
car polishing machines that exhibit two discs, although not
intended for cleaning purposes, which are rigidly arranged.

Previously disclosed through SE,B, 8302899-3
(publication number 432 352), for example, is a motor-driven
35 cleaning machine with a shaft, which exhibits two rotating

rollers, although these are so arranged as to act with their external envelope surfaces against the intended supporting surface, and the cleaning fluid is so arranged as to be supplied to the rollers from a reservoir. However, this
5 previously disclosed machine does not permit corners, etc., to be reached effectively or allow access to inaccessible cleaning surfaces, i.e. tight up to the edge of skirting boards and furniture.

A cleaning machine previously disclosed
10 through US, A, 3,013,288 exhibits a lower brush component supported by a machine head, which, by means of horizontally oriented screws, is permanently attached in a totally inaccessible fashion inside an outer casing, and which is
15 only capable of pivoting about a horizontal articulation, and has a fluid reservoir supported on a shaft, the function of which is to feed cleaning fluid by gravity through a pipe to the brushes positioned at a lower level than the reservoir.

It is accordingly not possible to remove the machine head easily for hand-held cleaning without using the
20 shaft of the machine, and it is not possible to work with the machine head at a higher level than the tank, since the machine has no pump in the tank and feeding of the cleaning fluid to the machine head functions only by gravity.

The principal object of the present invention
25 is thus, in the first instance, to make available an arrangement capable of solving the aforementioned problems.

The aforementioned object is achieved by means of an arrangement of the kind indicated above, which is characterized essentially in that the discs are supported by
30 a machine head mounted in such a way as to be capable of pivoting about articulations extending in pairs at an angle to one another, in that a bracket for the aforementioned machine head is so arranged on the outer front end of the shaft as to permit the detachable attachment of the machine
35 head to the shaft, so that the machine can be used hand-held

without a shaft, if required, in that the bracket, which constitutes a supporting element for the machine head, is formed by an accommodating component for the machine head that is supported by an outer bearing component, in that a
5 fluid reservoir with a pump is capable of attachment to the shaft, and in that the fluid supply line is connected to the aforementioned machine head.

The present invention is described below with reference to the drawings, in which

10 Figs. 1-3 and 4-9 show two separate illustrative embodiments of the arrangement for a cleaning machine, where

Fig. 1 shows a perspective view of a cleaning machine in accordance with the invention;

15 Fig. 1A shows the machine schematically in its operating position;

Fig. 2 shows the lower part of the machine;

Fig. 3 shows the attachment of cleaning pads to the machine;

20 Fig. 4 shows a perspective view of the second illustrative embodiment of the arrangement in its operating position;

Fig. 5 shows the machine head detached from the shaft;

25 Fig. 6 shows rotatable brush and polishing discs and their connection to the machine;

Fig. 7 shows a sectioned view of a disc in a position connected to the machine;

30 Fig. 8 shows a perspective view of a charged fluid reservoir in a position ready for connection to a shaft; and

Fig. 9 shows a schematic sectioned view of the reservoir and the shaft in the connected position.

An arrangement 1 for a cleaning machine 2
35 comprising a number of electrically powered rotating discs 3,

4, which are so arranged as to accommodate brushes, polishing pads, sanding pads, drying pads or other appropriate surface treatment devices 5 intended for attachment thereto on their flat surface, and a hand-held shaft 6 with a fluid supply line 7 for the supply of the intended cleaning agent in liquid form to the aforementioned discs 3, 4 and the intended surface 8 for cleaning, are clearly illustrated in Fig. 1.

The aforementioned arrangement 1 has at least two discs 3, 4 with separate directions of rotation 9, 10 in relation to one another and situated at a relative distance A from one another and so arranged as to carry a brush, etc., 5 on their respective free end 11 capable of being pressed into contact with the intended surface 8 to be cleaned if the need for cleaning arises. The discs 3, 4 are supported by a machine head 12, which contains an electric motor 13 and is mounted in such a way as to be capable of pivoting about pairs of articulations 14, 15 extending at an angle to one another. The aforementioned fluid supply line 7 is also connected to the aforementioned machine head 12.

Thanks to the counter-rotation, the machine 2 is retained in the intended position without wandering uncontrollably of its own accord in an undesired direction.

The components can be detachably attached to one another in a previously disclosed simple fashion by means of Velcro® attachment devices 50, 51 between the respective disc and brush, etc., 5

A bracket 16 adapted for the head 12 of the aforementioned machine is arranged in the area of the outer front end 6A of the shaft to permit detachable attachment of the machine head 12 to the shaft 6, if required. The aforementioned bracket 16 preferably includes a yoke-shaped accommodating part 17 with a form adapted to the machine head 12 around its periphery and supported by an outer bearing part 19 capable of pivoting about an outer bearing shaft 18, which bearing part is pivotable 20 in relation to the

aforementioned outer articulation 14. In this way, the machine 2 can be operated hand-held without a shaft 6, if required.

The machine head 12 can be surrounded and effectively retained, after having been introduced into the aforementioned accommodating part 17, by means of a strap 21, which exhibits means 22 of attachment in the form of, for example, Velcro® fabric, after the strap 21 has been attached to corresponding Velcro® fabric 22 on the accommodating part 17.

The sleeve 23 for the aforementioned outer bearing shaft 18 is accommodated by an inner bearing shaft 24 extending at right angles to the aforementioned outer bearing shaft 18.

Arranged between the two bearing shafts 18, 24 is a friction-actuated adjustment component 25, which is so arranged as to be capable of permitting adjustment of the two bearing shafts 18, 24 relative to one another at a desired angle for rigid attachment or for the adjustment of the shafts 18, 24, so that the components 14, 15 are free to rotate relative to one another against a certain resistance.

The aforementioned adjustment component 25 is formed, for example, by two flanges 26, 27 with holes in one articulation 15 and a centrally located attachment lug 28 with holes in the other articulation 14. The inner bearing shaft 24 is so arranged as to be accommodated in the holes, and a wing nut, wheel or nut, etc., is screwed onto one end 24A of the aforementioned shaft 24 in order, by so doing, to permit clamping of the flanges 26, 27 to the attachment lug 28. The other end of the shaft exhibits a head, although this is not shown here.

Arranged between the flanges 26, 27 and the attachment lug 28 are friction-increasing devices, preferably radial grooves, which increase the clamping force in conjunction with clamping.

A fluid reservoir 29 with a pump 30 is capable of attachment to the shaft 6, and the reservoir 29 can easily be connected to an electrical connection 33 on the shaft 6 and the fluid line 7 via an electrical cable 31 and a fluid line connector 32.

A battery of the kind that contains a gel or some other suitable kind of battery can be accommodated inside a portable bag 43 that the person using the invention can easily carry with him/her during the period when cleaning is taking place, for example over the shoulder or in a back pack. A battery 34 of this kind or the electrical mains supply can be detachably attached via a cable 35 to the outer part 6B of the shaft at a handle 36 to an electrical connection 37 provided at that point.

The shaft 6, which consists of a rod, finally exhibits a length such that it corresponds to the length normally exhibited by a scrubbing brush or a long-handled brush. At its end 6A facing away from the handle part 36, the shaft 6 has a threaded arrangement 38 to permit detachable connection of the shaft 6 to a sleeve-shaped end component 39 on a component 16 for supporting the machine head.

When in the effective cleaning position, the machine head 12 is thus capable, after switching on the motor 13 by means of a starting switch 40 and/or 40¹, of causing the discs 11 in question to rotate, cleaning the intended surface 8, and being pivoted both about the axis 18 of the outer pivot link 14 in the direction of pivoting 20, and about the axis 24 of the inner pivot link 15 in the desired direction of pivoting 41, by actuation of the shaft 6. If necessary, a switch 42 is actuated to start the tank pump 30 and cause a desired quantity of cleaning fluid 43 to be sprayed from the tank 29 onto the floor 8, for example polish, detergent, water or wax, etc.

The illustrative embodiment of the arrangement 101 for an aforementioned cleaning machine 102, as

illustrated in Figs. 4-9, comprises a bracket 116 made of a plastic material that is curved and resilient and exhibits mutually opposing snap devices 175, 176 on its respective free end to snap into engagement around each projecting part 177 of the machine head 112, thereby being securely clamped around it along an intended fixing part 178. The aforementioned bracket 116 is supported at its one end by the shaft 106 of an outer supporting part 119.

The discs 103, 104 preferably exhibit an opening 181, which is intended to accommodate a rotating shaft 182 in the machine head 112, and the aforementioned opening 181 and shaft 182 exhibit congruent form with a multi-sided periphery, for example in the form of a polygon such as a pentagon.

The rotating shaft 182 exhibits a clamping component 183 on its free end, for example the end of the shaft is slotted so that it can be compressed during connection and spring out again afterwards.

Situated internally in the accommodating opening 181 of the aforementioned discs 103, 104, which can hold a brush, etc., 105, is an inward-projecting thickening 184, such as an annular rim or a number of protrusions, within which the clamping component 183 is adapted to be accommodated.

The shaft 106 is preferably so arranged as to be adjustable in the longitudinal sense and lockable at the desired length by means of an actuation mechanism 179, for example a spring-assisted button 200, which is adjustable along a number of notches 201 on a section of tube 202 inserted inside the shaft.

A shaped fluid reservoir 129, which exhibits a longitudinal external recess 203 shaped to fit the shaft 106, inside which the shaft 106 is capable of being accommodated, is capable of being clamped around the shaft 106 with the help of an enlargement 204 attached to the shaft 106. The

aforementioned enlargement 204 can be screwed securely to the shaft 106 by means of a number of clamping rings 205 and is capable of interacting with a number of retaining bodies 206, for example balls in holes, preferably spring-assisted transversely in relation to the shaft, accommodated in a recess 205 shaped to fit the enlargement 204.

A pump 130, present inside which is a suction hose 207 that reaches to its bottom, is attached to the tank in accordance with the foregoing, so that fluid can be pumped to the machine head 12 in all positions.

The articulations 115, 115A between the bracket 116 for the machine head 112 and the shaft 106 are also capable of actuation by a lock 180 so arranged as to change the angle between the shaft 106 and the aforementioned bracket 116. The aforementioned lock 180 is so arranged as to be released by means of a button to vary the angle, so that the machine can easily be adjusted to suit the person who is to use the machine.

Extending at right angles from the axis of articulation of the aforementioned lock is an articulation 114, about which the bracket 116 and the machine head 112 supported by it can rotate when the shaft 106 is caused to rotate. An upper handle 136 contains the switch 140, 142 for the motor and the pump in accordance with the above example.

The invention is not restricted to the illustrative embodiments shown in the drawings and described above, but can be modified within the scope of the Patent Claims without departing from the idea of invention.

P a t e n t C l a i m s

5 1. Arrangement (1; 101) for a cleaning machine
(2; 102) comprising at least two disks (3; 103, 4; 104),
mounted in mutually opposing directions of rotation (9, 10)
and at a relative distance (A) from one another and so
arranged as to carry a brush (5; 105) or other surface
10 treatment device on their respective free end (11) for
pressing into contact with the intended surface (8) to be
cleaned, and a hand-held shaft (6; 106) with a fluid supply
line (7; 207) for the supply of cleaning fluid to the
aforementioned discs (3; 103, 4; 104), *characterized in that*
15 the discs (3; 103, 4; 104) are supported by a machine head
(12; 112) supported in such a way as to be capable of
pivoting about articulations (14, 15; 114, 115) extending in
pairs at an angle to one another, in that a bracket (16; 116)
for the aforementioned machine head (12; 112) is so arranged
20 on the outer front end (6A) of the shaft as to permit the
detachable attachment of the machine head (12; 112) to the
shaft (6; 106), so that the machine (2; 102) can be used
hand-held without a shaft (6; 106), if required, in that the
bracket (16; 116), which constitutes a supporting element for
25 the machine head, is formed by an accommodating component for
the machine head (12; 112) that is supported by an outer
bearing component (19; 119), in that a fluid reservoir (29;
129) with a pump is capable of attachment to the shaft (6;
106), and in that the fluid supply line (7; 207) is connected
30 to the aforementioned machine head (12; 112).

2. Arrangement as claimed in Patent Claim 1,
characterized in that the outer bearing part (19) is
pivotable about an outer bearing shaft (18).

3. Arrangement as claimed in Patent Claim 2,
characterized in that the sleeve (23) for the aforementioned
outer bearing shaft (18) is accommodated by an inner bearing
shaft (24) extending at right-angles to the aforementioned
5 outer bearing shaft (18).
4. Arrangement as claimed in Patent Claim 3,
characterized in that arranged between the two bearing shafts
(18, 24) is a friction-actuated adjustment component (25),
which permits adjustment of the two bearing shafts (18, 24)
10 relative to one another at a desired angle for rigid
attachment or for the adjustment of the shafts (18, 24) so
that they are capable of rotating relative to one another
against a certain resistance.
5. Arrangement as claimed in Patent Claim 4,
15 *characterized in that* the adjustment component (25) is formed
by two flanges (26, 27) with holes and a centrally located
attachment lug (28) with holes, and the inner bearing shaft
is accommodated in the holes, and in that a wing nut or
wheel, etc., is screwed onto one end (24A) of the
20 aforementioned shaft (24) in order to clamp the flanges (26,
27) to the attachment lug (28).
6. Arrangement as claimed in Patent Claim 5,
characterized in that friction-increasing devices, preferably
radial grooves, are arranged between the flanges (26, 27) and
25 the attachment lug (28).
7. Arrangement as claimed in one or other of the
above Patent Claims, *characterized in that* a battery (34) or
the electrical mains supply can be attached via a cable (35)
to the outer part (6B) of the shaft, where an electrical
30 connection (37) is provided.
8. Arrangement as claimed in one or other of the
above Patent Claims, *characterized in that* the shaft (6)
exhibits a length corresponding to the length of a scrubbing
brush and has a threaded arrangement (38) at its end (6A)

facing away from the handle part (36) to permit detachable connection to a sleeve-shaped end component (39) on the component (16) for carrying the machine head.

9. Arrangement as claimed in one or other of the
5 above Patent Claims, *characterized in that* the accommodating component (16) for the machine head (12) is in the form of a strap.

10. Arrangement as claimed in Patent Claim 1,
characterized in that the bracket (16) includes an
10 accommodating part (17) with a form adapted to the machine head (12) around its periphery.

11. Arrangement as claimed in Patent Claim 10,
characterized in that the bracket (116) is curved and
resilient and exhibits mutually opposing snap devices (175,
15 176) on its respective free end to snap into engagement around each projecting part (177) of the machine head (112), thereby being securely clamped around it along a fixing part (178).

12. Arrangement as claimed in Patent Claim 1,
20 *characterized in that* the shaft (106) is adjustable in the longitudinal sense and lockable at the desired length by means of an actuation mechanism (179).

13. Arrangement as claimed in Patent Claim 1,
characterized in that the discs (103, 104) exhibit an
25 accommodating opening (181) for a rotating shaft (182) in the machine head (112), and in that the aforementioned opening (181) and shaft (182) exhibit congruent form with a multi-sided periphery, for example a polygon such as a pentagon.

14. Arrangement as claimed in Patent Claim 13,
30 *characterized in that* the rotating shaft (182) exhibits a clamping component (183) on its free end, for example the end of the shaft is slotted so that it can be compressed during connection.

15. Arrangement as claimed in Patent Claim 14,
characterized in that present internally in the accommodating
opening (181) of the aforementioned discs (103, 104) is an
inward-projecting thickening (184), such as an annular rim or
5 a number of protrusions, within which the clamping component
(183) is adapted to be accommodated.

16. Arrangement as claimed in Patent Claim 1,
characterized in that the fluid reservoir (129) exhibits a
longitudinal external recess (203) shaped to fit the shaft
10 (106), inside which the shaft is capable of being
accommodated and of being clamped with an enlargement (204)
attached to the shaft (106).

17. Arrangement as claimed in Patent Claim 16,
characterized in that the enlargement (204) is screwed
15 securely to the shaft (106) by means of clamping rings (205)
and is capable of interacting with a number of retaining
bodies (206) spring-assisted preferably transversely in
relation to the shaft (106), accommodated in a recess (205)
shaped to fit the enlargement (204).

20 18. Arrangement as claimed in Patent Claim 1,
characterized in that the articulations (115, 115A) between
the bracket (116) for the machine head (112) and the shaft
(106) incorporate a lock (180) to change the angle between
the shaft (106) and the aforementioned bracket (116).

25 19. Arrangement as claimed in Patent Claim 18,
characterized in that extending at right angles from the axis
of articulation of the aforementioned lock is an articulation
(114), about which the bracket (116) and the machine head
(112) supported by it can rotate.

1 / 9




FIG. 1

2 / 9







FIG. 2

3 / 9

FIG.3



4 / 9



5/9




FIG. 5

6 / 9




FIG. 6

7 / 9




FIG. 7

8 / 9




FIG. 8

9/9




FIG. 9

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 98/01420

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: A47L 11/283, A47L 11/03, A47L 11/16

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: A47L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 3013288 A (R.I. LAPPIN), 19 December 1961 (19.12.61), figures 1,2,7 --	1
A	SE 502450 C2 (SWISH AB), 23 October 1995 (23.10.95), figures 1,2 --	1
A	SE 505718 C2 (LARS JOHNNY ENSSON), 6 October 1997 (06.10.97), detail 28 --	1
A	FR 2229511 A (SABLE FRERES INTERNATIONAL (S.A.)), 13 December 1974 (13.12.74), detail 6 --	4



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

30 October 1998

Date of mailing of the international search report

10 4 - 11 - 1998

Name and mailing address of the ISA/

Swedish Patent Office

Box 5055, S-102 42 STOCKHOLM

Facsimile No. + 46 8 666 02 86

Authorized officer

Jan-Axel Ylivainio

Telephone No. + 46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.
PCT/SE 98/01420

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	FR 1267092 A (DIETHELM & CO. A. G.), 5 June 1961 (05.06.61), details 5A,6A,7 -- -----	5

INTERNATIONAL SEARCH REPORT
Information on patent family members

05/10/98

International application No.
PCT/SE 98/01420

Patent document cited in search report			Publication date	Patent family member(s)	Publication date
US	3013288	A	19/12/61	NONE	
SE	502450	C2	23/10/95	SE 9203793 A	18/06/94
SE	505718	C2	06/10/97	SE 9504178 A	24/05/97
FR	2229511	A	13/12/74	NONE	
FR	1267092	A	05/06/61	NONE	